

Technical Characteristics

Voltage circuit

Dual voltage.....230/400 V (-10/+15%)
 Frequency.....45....65Hz (automatic adjust)
 Power consumption..... 5 VA
 Current circuit (isolated):
 External transformer (not included)...../5 A (on request 1 A)
 Power consumption.....0.5 VA
 Internal relays
 Steps relays.....4.....8/14
 Alarm relay.....Optional
 Output contacts AC 11 le/Ue..... 1 A/110 Vdc
 Electrical endurance.....2 x10⁵ operations
 Mechanical characteristics
 Dimensions (mm).....-MCX-8 :96 x96/144 x144
 -MCX-14 : 144 x144
 Weight.....-MCX-8 : 532g (96 x96) / 656g(144
 -MCX-14 : 656 g
 Connection.....Plug-in connector
 Degree of protection.....IP 41
 Climatic range.....-10 to 50°C

MCX Advance Controller

Output Relays	Types	
	96×96mm	144×144mm
	With Alarm	With Alarm
4	MCX-8-4-96/A	MCX-8-4-144/A
6	MCX-8-6-96/A	MCX-8-6-144/A
8	MCX-8-8-96/A	MCX-8-8-144/A
10	-----	MCX-14-10-144/A
12	-----	MCX-14-12-144/A
14	-----	MCX-14-14-144/A